

PH LOGIX

OPTIMISE THE EFFECTIVENESS OF YOUR
SANITISER BY AUTOMATICALLY MAINTAINING
PERFECT pH BALANCE IN YOUR POOL

AUTOMATICALLY DOSES
AND MAINTAINS SAFE
PH/ACID LEVELS

PROTECTS POOL
SURFACE AND
EQUIPMENT FROM
SCALE AND
CORROSION

PREVENTS pH FROM
FLUCTUATING IN AND
OUT OF BALANCE

STRONG & DURABLE
COMMERCIAL GRADE
PERISTALTIC TUBE
AND ROLLER

NO PROBE OR
CALIBRATION
REQUIRED

NEVER OVERDOSE
YOUR POOL WITH
ACID AGAIN



1 YEAR*
FULL WARRANTY

CAS | CRYSTAL
AQUATIC SYSTEMS

PH LOGIX

PH LOGIX IS THE PERFECT COMPANION FOR THE VAPURE SALT AND MINERAL SYSTEM

SUITABLE FOR ALL POOL SURFACES

WORKS WITH HIGH AND LOW FLOW FILTRATION SYSTEMS

SIMPLE TO OPERATE

EASY INSTALLATION - PLUG AND PLAY

PROVEN ACID DOSING PUMP TECHNOLOGY

SPECIFICATION

Volts Input (Vac)	220-245
Amps Input - Max. (Aac)	1.00
Total Power Consumption (W)	13W Motor - 20W Total
Frequency (Hz)	50
pH Controller Dimensions (mm)	135W x 225H x 123D
Output Controlled by Sanitiser (LPH)	0-1.0
Rated Pressure (kPa)	350
Squeeze Tube	Tygon® Norprene® (Commercial spec)
Case Pump Inspection Window	Clear acrylic viewing window
Motor Speed (RPM)	10
Non-Return Injector Valve	PVC with Viton sleeve
Tubing	4m x 4mm PVC
Roller Block	Heavy-duty PVC
Casing Materials	Glass filled polypropylene
Power Cord	Approved piggy-back type
Wall Mounting	Click ON - Clip OFF
Water Connection Fitting	Clear Acrylic Interface to 40/50mm pipe
Water Flow Rate (L/min)	80-650
Ingress Protection Rating	IP34
Unit Shipping Dimensions (mm)	140W x 335H x 130D
Nett Weight (kg)	2.5



7 City Link Drive Carrara Queensland, 4211
Ph: +61 7 5522 9763 Email: info@crystalas.com

www.crystalas.com

©2021 CAS | Crystal Aquatic Systems. All rights reserved. Unauthorised reproduction is prohibited by law. While every effort is made in maintaining the accuracy of the information contained in this catalogue, the same information is subject to change either by circumstances out of our control or at the discretion of management without further notice.

Your Local Agent